

In the present invention, at least one of the flexographic printing stations prints an image with liquid vehicle slurry containing an encapsulated essence. In another embodiment, at least one of the printing stations prints an image with a water-based liquid vehicle containing suspended particles that are either uniform or nonuniform in size. The suspended particles may be metallic particles up to substantially 16 microns in diameter.

The present invention may also use the metallic color printing process as disclosed in commonly assigned U.S. Pat. No. 5,370,976 incorporated herein by reference in its entirety.

In one aspect, the novelty of the present invention is to create a flexographic printing station that can be used at one of a plurality of printing stations in a continuous in-line process and in which, at a subsequent printing station, a lithographic process may be used to print over the liquid vehicle printed by the flexographic station.

Thus, there has been disclosed an apparatus for a combined lithographic/flexographic printing process that includes a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process and wherein one of the stations prints a first color image using the flexographic process and at least one of the successive printing stations prints a second color image over the first color image using the lithographic process in the continuous in-line process.

While the invention has been described in connection with a preferred embodiment, it is not intended to limit the scope of the invention to the particular form set forth, but, on the contrary, it is intended to cover such alternatives, modifications, and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

We claim:

1. Apparatus for a combined lithographic/flexographic printing process comprising:

- a substrate;
- a plurality of successive printing stations for printing color images on the substrate in a continuous in-line process;
- one of said stations comprising a flexographic printing station for printing a liquid vehicle image on said substrate with a slurry containing an encapsulated essence using the flexographic process;
- at least one of said successive printing stations being a lithographic printing station; and
- an overcoating applied over the liquid vehicle image on the printed substrate at at least one of said successive lithographic printing stations using the lithographic process in said continuous in-line process.

2. Apparatus as in claim 1 wherein said overcoating is an aqueous overcoating.

3. Apparatus as in claim 1 wherein said overcoating is an ultraviolet ink overcoating.

4. Apparatus as in claim 1 wherein:
said substrate is a paper sheet; and
said apparatus includes a sheet feeder.

5. Apparatus as in claim 1 wherein:
said substrate is a web; and
said apparatus includes a web feeder.

6. Apparatus for a combined lithographic/flexographic printing process comprising:

- a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process;

00315796-052099

00315796-052099

Claims attached

one of said stations comprising a flexographic printing station printing an aqueous-based vehicle image using the flexographic process to form a metallic coating; a suspended metallic material being included in said aqueous-based vehicle image; and

at least one of the successive printing stations comprising an offset lithographic printing station printing a color image over the aqueous-based vehicle image using the offset lithographic process in said continuous in-line process.

7. Apparatus as in claim 6 wherein said suspended material includes uniform-sized metal particles to form said metallic coating.

8. Apparatus as in claim 6 wherein said suspended material includes nonuniform-sized metal particles to form said metallic coating.

9. Apparatus as in claim 6 further including: said flexographic printing station including a plate cylinder having a flexographic plate thereon, a blanket cylinder, and an impression cylinder;

a flexographic plate image transferred from said plate cylinder to said blanket cylinder, said image being formed of said metallic coating, said blanket cylinder transferring said metallic coating to said impression cylinder for printing said flexographic plate image on said substrate; and

an anilox roller associated with said flexographic plate for supplying said aqueous-based vehicle containing said suspended metallic material to said flexographic plate.

10. Apparatus for creating a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station for printing a first color image using the flexographic process; and

at least one of the successive printing stations comprising an offset lithographic printing station for printing a second color image over the first color image using the offset lithographic process in said continuous in-line process.

11. Apparatus as in claim 10 further including:

said flexographic printing station including a plate cylinder, a blanket cylinder, and an impression cylinder;

a flexographic plate on said plate cylinder;

an anilox roller associated with said flexographic plate for supplying a first color to said flexographic plate to form said first color image; and

said blanket cylinder receiving said first color image from said plate cylinder and transferring said first color image to said impression cylinder for printing on said substrate.

12. Apparatus for creating a combined lithographic/flexographic printing process comprising:

a substrate;

a plurality of successive printing stations for printing color images on the substrate in a continuous in-line process;

at least two successive ones of said printing stations being flexography stations and comprising:

(1) a supply of liquid coating;

(2) a plate cylinder associated with a blanket cylinder, said plate cylinder having a flexographic plate thereon;

00315796-00000

00315796-00000

(3) an anilox roller associated with said liquid supply coating and said plate cylinder for delivering said liquid coating to said flexographic plate to form an image for transfer to said blanket cylinder;

(4) an impression cylinder for receiving said liquid coating image transferred from said blanket cylinder and printing said image on said substrate, said at least two flexography stations printing the same liquid coating image in sequence and in superimposed relationship; and

at least one offset lithographic printing station for receiving said substrate and printing over said liquid coating image.

13. Apparatus as in claim 12 wherein said liquid coating image printed on said substrate is a white color ink.

14. Apparatus as in claim 12 further including an air dryer associated with each of said impression cylinders on said flexography stations, said air dryer having sufficient air velocity for drying said liquid coating before the substrate is transferred to the successive printing station in said continuous in-line process.

15. Apparatus for a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process, said printing stations including both lithographic and flexographic printing stations;

a blanket cylinder at at least a first one of said flexographic printing stations;

flexographic ink-providing means at said at least first one of said flexographic printing stations for applying a flexographic ink to said blanket cylinder to form an image;

a substrate for receiving said flexographic ink image transferred from said blanket cylinder; and

at least one subsequent lithographic printing station in said in-line process for receiving said image printed substrate and printing an additional colored ink image on said substrate on top of said flexographic ink image using offset lithography.

16. Apparatus as in claim 15 further comprising:

a plate cylinder at said at least first one of said flexographic stations;

a flexographic plate on said plate cylinder for receiving and transferring said flexographic ink to said blanket cylinder; and

said flexographic ink-providing means including a flexographic ink supply and an anilox roller associated with said flexographic ink supply for transferring said flexographic ink to said flexographic plate.

17. Apparatus for a combined lithographic/flexographic printing process for printing a multicolored image comprising:

a plurality of successive printing stations for printing color on a substrate in a continuous in-line process, said printing stations including both lithographic and flexographic printing stations;

at least one of said flexographic printing stations having:

(1) a plate cylinder and a blanket cylinder, said plate cylinder including a flexographic plate having an image thereon for transferring a flexographic color ink image to said blanket cylinder;

(2) an etched anilox roller for applying a flexographic color ink to said flexographic plate on said plate cylinder;

09315796-052099

09315796-052099

(3) an impression cylinder in ink-transfer relationship with said blanket cylinder for transferring said flexographic color ink image from said blanket cylinder to said substrate; and

at least one of said succeeding printing stations being a lithographic printing station using offset lithography for printing additional colored ink images on top of said flexographic ink image.

18. Apparatus as in claim 17 wherein said additional colored ink images are formed with lithographic inks.

19. Apparatus as in claim 17 wherein said colored ink images are formed with waterless inks.

20. Apparatus as in claim 17 further including an air dryer adjacent to said impression cylinder for drying the flexographic ink image transferred to said substrate before said additional colored ink images are printed thereon.

21. Apparatus as in claim 17 further including halftone printing plates for printing said colored ink images.

22. Apparatus as in claim 17 wherein said flexographic ink image and said colored ink images are printed as solid colors and/or with halftone printing plates in sequence and in registry in said successive printing stations to produce said multicolored image on said substrate.

23. Apparatus as in claim 17 wherein said printing apparatus includes a sheet-fed press.

24. Apparatus as in claim 17 wherein at least one of said flexographic printing stations prints said flexographic ink image with liquid vehicle slurry containing an encapsulated essence.

25. Apparatus as in claim 17 wherein at least one of said printing stations prints said flexographic ink image with a water-based liquid vehicle containing suspended particles.

26. Apparatus as in claim 25 wherein said suspended particles are uniform in size.

27. Apparatus as in claim 25 wherein said suspended particles are nonuniform in size.

28. Apparatus as in claim 25 wherein said suspended particles are metallic particles.

29. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

providing a plurality of successive lithographic/flexographic printing stations for printing colored ink images on a substrate;

printing a flexographic ink image on said substrate at at least one of said flexographic stations;

transferring said printed substrate to at least one subsequent printing station in said continuous in-line process; and

printing colored ink images on top of said flexographic ink image at at least one of said subsequent lithographic printing stations with an offset lithographic process.

30. A method as in claim 29 further comprising the step of drying said flexographic ink image on said substrate with an air dryer prior to printing said colored ink images thereon.

31. A method as in claim 29 further including the step of printing a coating on top of said colored ink images at one of said plurality of subsequent printing stations.

32. A method as in claim 29 wherein said colored inks forming said colored ink images are waterless.

33. A method as in claim 29 wherein said colored inks forming said colored ink images are in a solvent-based liquid vehicle.

00345796 652099

000250 96757660

34. A method as in claim 29 further including the steps of:
printing a slurry on said substrate at any of said printing
stations in said continuous in-line process;

5 using an encapsulated essence in said slurry; and
printing an overcoating over said slurry at a subsequent
printing station in said in-line process to protect said
essence.

35. A method as in claim 34 further including the step of
10 printing an aqueous-based coating over said slurry.

36. A method as in claim 34 further including the step of
printing an ultraviolet coating over said slurry.

37. A method of combining offset lithography and flexo-
graphic printing in a continuous in-line process comprising
the steps of:

15 providing a substrate;

applying a flexographic ink to a blanket cylinder in a
pattern with a coating head at a first flexographic
printing station;

20 transferring said pattern of flexographic ink from said
blanket cylinder to the substrate; and

printing a waterless ink pattern over said flexographic ink
pattern on said substrate at at least one subsequent
offset lithographic printing station in said continuous
25 in-line process.

38. A method of combining lithography and flexographic
printing in a continuous in-line process comprising the steps
of:

30 printing an aqueous-based vehicle image having sus-
pended particles therein on a substrate at a first flexo-
graphic printing station;

transferring said image printed substrate to at least one
additional printing station in said continuous in-line
35 process; and

printing additional colored ink images on said printed
substrate over said aqueous-based vehicle image in an
offset lithographic process at said at least one additional
printing station in said in-line process.

40 39. A method of combining lithography and flexographic
printing in a continuous in-line process comprising the steps
of:

(1) providing a plurality of successive printing stations for
45 printing liquid vehicle images on a substrate in said
in-line continuous process;

(2) utilizing an anilox roller to transfer a liquid ink as said
liquid vehicle to a flexographic plate image at at least
one of said printing stations;

50 (3) printing said liquid ink from said flexographic plate
image to a substrate;

(4) transferring said printed substrate with said liquid ink
image to a subsequent printing station in said in-line
printing process;

55 (5) repeating steps (2)-(4) at subsequent printing stations
in said in-line process to achieve a desired opacity ink
image on said substrate; and

(6) printing an ink pattern over said flexographic ink
image using an offset lithographic process.

60 40. A method as in claim 39 further including the step of
additionally printing colored ink images over said liquid ink
image on said substrate at subsequent ones of said printing
stations in said in-line process.

41. A method as in claim 40 wherein said liquid ink is an
65 opaque white color.

* * * * *

00315796.052099

00315796.052099